



ENGINEERING BULLETIN

Subject:

Z-FLEX'S Z-DENS VENT SYSTEMS APPROVED FOR USE WITH PRESTIGE

Date: 8/17/2015

Z-Flex's Z-DENS Polypropylene Vent Systems are now approved for use with Prestige Boilers. Z-DENS is ULC-S636 approved and offers both single wall rigid as well as flex venting options.

Follow all Polypropylene Vent Instructions in the current Prestige Vent Supplement as well as Z-Flex's Z-DENS installation instructions. Consult the Prestige Vent Supplement for required vent diameter as well as maximum vent lengths. The Prestige Vent Supplement will be updated in the near future to include the following:

	Appliance Vent Adapter	
2" (60mm) Z-Flex Z-DENS Polypropylene Venting	2ZDCPVCG3 & 2ZDR32	
3" (80mm) Z-Flex Z-DENS Polypropylene Venting	2ZDCPVCG3	
4" (100mm) Z-Flex Z-DENS Polypropylene Venting (Exc. Solo 399)	c. Solo 399) 2ZDCPVCG3 & 2ZDI34	
4" (100mm) Z-Flex Z-DENS Polypropylene Venting (Solo 399)	2ZDCPVCG4	

	Rigid Termination	Flex Termination
	Options	
2" (60mm) Z-Flex Z-DENS Polypropylene Venting	2ZDE245UV	2ZD2FLK2
	2ZDE287UV	
	2ZDTT2 & 2ZDP210UV	
	2ZDP220UV & 2ZDES2	
3" (80mm) Z-Flex Z-DENS Polypropylene Venting	2ZDE345UV	2ZD2FLK3
	2ZDE387UV	
	2ZDTT3 & 2ZDP310UV	
	2ZDP320UV & 2ZDES3	
4" (100mm) Z-Flex Z-DENS Polypropylene Venting	2ZDE445UV	2ZD2FLK4
	2ZDE487UV	
	2ZDTT4 & 2ZDP410UV	
	2ZDP440UV & 2ZDES4	

Please contact Triangle Tube Technical Support or Z-Flex (800-654-5600) with any questions.



Freeway Center - 1 Triangle Lane - Blackwood, NJ 08012 Tel: 856 228 8881 - Fax: 856 228 3584 - e-mail: info@triangletube.com