

According to Charlotte Pipe & Foundry Company's Plastics Technical and Installation Manual(Updated August 24, 2023) WARNINGS (page 88)

**Never use PVC cellular core, ABS cellular core pipe or ConnecTite<sup>®</sup> fittings for combustion gas venting.**

**Only use ABS/ CPVC/PVC pipe and fitting for the conveyance of fluids as defined within the applicable ASTM standards.**

**Never use ABS/CPVC/ PVC pipe and fittings for the conveyance of gasses.**

The following link provides additional information:

[TM-PL.pdf \(charlottepipe.com\)](#)see page 88)

According to Napco Pipe & Fittings Plumbing Product Specification for ASTM D1785/D2665 Sch. 40 PVC Pressure/DWV Pipe (document PL-PS-001-US-EN-0119.2):

**WARNING: Flue gas temperature should not exceed 140° Fahrenheit. PVC pipe exposed to temperatures higher than 140° Fahrenheit may melt or change shape, resulting in leakage of exhaust fumes and property damage.**

The following link provides additional information:

[https://www.westlakepipe.com/sites/default/files/media/PL-PS-001-US-EN-0522.1\\_D1785-D2665-Sch40-Sch80.pdf](https://www.westlakepipe.com/sites/default/files/media/PL-PS-001-US-EN-0522.1_D1785-D2665-Sch40-Sch80.pdf)

**U.S.A.**

20 Commerce Park North, Bedford, NH 03110-6911  
Tel: 603.669.5136 Fax: 888.889.3539 Toll Free: 800.654.5600

**CANADA**

452 Atwell Drive, Etobicoke, ON M9W 5C3  
Tel: 416.679.0045 Fax: 416.679.0051

rev. 08.2023