

A Direct Vent System that does not Compromise Indoor Air Quality Designed for use when converting existing wood-burning fireplaces into gas fireplace inserts

In terms of safety, efficiency and versatility, Direct Vent fireplaces have several advantages over traditional fireplaces. Direct Vent Systems use outdoor air instead of indoor air for combustion. Using indoor air for combustion can de-pressurize the living space and potentially pull harmful flue gases back into the home. With a Direct Vent System, outside air is drawn in for combustion while flue gas is exhausted outside. The natural flow of heat creates a convection loop; as hot air exits the pipe, cooler, denser air is pulled back to the burner.

Safety - Z-Flex Triple Lock[®], acknowledged as the best flexible duct construction method for strength and durability, provides piece of mind that flue gases, through continuous length flexible gas vent, are being safely vented outside the living space. In addition, computer added design and construction methods help produce aesthetically pleasing and high performance system components.

Versatility - Direct Vent Systems are easy to install. Continuous length Triple Lock[®] Flexible Gas Vent provides only two connection points; *Insert and Termination*. The flexible venting is quickly and easily routed through straight or offset existing masonry chimneys. *Extreme Weather, Decorative and Low Profile Terminations* options.

Extreme Weather Kit



Decorative Kit



Low Profile Kit



Direct Vent Systems



Direct Vent Co-Linear Flexible Liner Kit with Extreme Weather Cap/Flashing

includes:

- Chimney Liners (Exhaust and Intake)
- Extreme Weather Cap/Flashing
- Self-tapping Screws



Direct Vent Co-Linear Flexible Liner Kit with Decorative Cap/Flashing

includes:

- Chimney Liners (Exhaust and Intake)
- Decorative Cap/Flashing
- Self-Tapping Screws



Model DVI-LP Direct Vent Co-Linear Flexible Kit with Low Profile Cap

includes:

- Chimney Liners (Exhaust and Intake)
- Low Profile Cap
- Flashing
- Self-tapping Screws
- 4x3 Reducer (2SVI4335LP)



Part ID	Description	Exhaust size	Intake size
2DVI335D	DV Co-Linear 3/3 Decorative Kit X 35 Ft	3 in.	3 in.
2DVI335LP	DV Co-Linear 3/3 Low Profile Kit x 35 Ft	3 in.	3 in.
2DVI335X	DV Co-Linear 3/3 Extreme Weather Kit X 35 Ft	3 in.	3 in.
2DVI435D	DV Co-Linear 4/3 Decorative Kit X 35 Ft	4 in.	3 in.
2DVI435LP	DV Co-Linear 4/3 Low Profile Kit x 35 Ft	4 in.	3 in.
2DVI435X	DV Co-Linear 4/3 Extreme Weather Kit X 35 Ft	4 in.	3 in.

The Flexible Venting Solutions Specialist

Z-FLEX® part of the Novaflex Group of companies, is the leading manufacturer of specialty venting systems for furnaces, boilers, water heaters, oil heaters, fireplaces and more.

Z-FLEX® has been providing flexible answers to gas, oil, pellet and wood venting applications since 1979, having pioneered flexible chimney liner solutions and special gas vent (AL 29-4C®). Constant innovations in materials and construction create products that deliver:

- Superior performance and increased efficiency
- Easier handling and faster, simpler installation
- Greater reliability, safety and increased service life

The Novaflex Group® is a privately held company committed to continuous advancement in venting solutions. Novaflex Group® has one of the broadest product ranges available in the marketplace for the HVAC, industrial venting and hose industries.

Throughout more than forty years, Novaflex® has earned a solid reputation for providing innovative and high quality products.

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete Terms and Conditions of Sale located on our web sites at: www.novaflex.com | www.z-flex.com | www.flexmaster.com.

U.S.A.

20 Commerce Park North
Bedford, New Hampshire
03110-6911
tel: 603.669.5136
fax: 603.669.0309
www.z-flex.com email sales@z-flex.com


CANADA

452 Attwell Drive
Etobicoke, ON M9W 5C3
tel: 416.679.0045
fax: 416.679.0051

Distributed by:



Direct Vent System



ver 11.2023