

Smoothcore™ Triple Lock®

Triple Lock® Smoothcore™ All Fuels Chimney Liner

- Eliminates the turbulence that's inherent with corrugated liners, improving draft
- Resists corrosive attack by not impeding the flow of condensate down the liner and less opportunity for soot to accumulate
- Patented Triple-Lock® design won't pull apart during installation, or under extreme heat conditions

Proprietary 316Ti Plus Titanium stainless steel ensures indefinite service life and safety in containing creosote fires. cULus tested and listed by UL to UL1777 and ULC S635



Z-FLEX®
CHIMNEY & VENTING SOLUTIONS

Smoothcore

All Fuel Stainless Steel Kit




Smoothcore Kit Includes:

Smoothcore Stainless Steel Liner
Chimney Flashing
Rain Cap
Z-Lok Tee
Part No.: 2ZFCKIT
Dia.: ____ | Lgth.: ____
Dia.: 5"-8" | Lengths: 50'

Kit must be insulated for wood burning applications.



Smoothcore™ Flex Liner



Order No: 2ZLSCXX _ _

Z-Lok Tee



Order No: 2ZFTJ _ _
(dia)

Flex Ready Pellet Tee with 3" branch



Order No: 2ZPT43

Note: This style tee is to be used with Z-Flex flexible liner. Refer to rigid tee for use with rigid liner or when stacking two tees together. 3" and 10" nose spouts are not removable.

Insulating Blanket with Wrap and Gear Clamps



Order No: 2INSKIT _ _ _ _
(dia) (lgth)

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com | www.z-flex.com | www.flexmaster.com.

U.S.A. tel: 603.669.5136 fax: 603.669.0309
CANADA tel: 416.679.0045 fax: 416.679.0051
www.z-flex.com • email sales@z-flex.com