

Novaflex®

Diesel Exhaust Fluid Hose

Novaflex 4203BE

Diesel Exhaust Fluid (DEF) Transfer Hose

This is a 200psi working pressure rated hose specifically designed to transfer DEF fluids. This suction and discharge hose has an EPDM construction designed to be resistant to the effects of the media transferred. This hose is flexible and excellent for reel applications.

Specifications

Tube: Specially formulated EPDM

Reinforcement: Plies of cord and helix wire

Cover: Blue EPDM

Length: 50 ft & 100 ft plain ends/boxed

Temperature Range: -40° (-40°C) to +210°F (+98°C)

Banding: DEF Hose, 4203BE, 200psi, 210° max temp, urea fluid



Specification Chart

Part No.	I.D.	MBR (in)	Vacuum HG	Plies	WP psi	WT LBS/FT
4203BE-00750-00	¾	2.5	Full	2	200	0.48
4203BE-01000-00	1	3	Full	2	200	0.60
4203BE-01500-00	1½	6	Full	2	200	0.63
4203BE-02000-00	2	6	Full	2	200	1.52

Due to continuous improvements, technical data subject to change without notice. All hose and duct manufactured by Novaflex® are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation.

10.2016

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IND 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905) 686-8349
800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk