

Novaflex®

AF Liner

Novaflext AF Liner

A low pressure hose, designed to be extremely lightweight, but offer high flexibility and abrasion resistance in vacuum and discharge applications.

Specifications

Tube: V_8'' ultra high abrasion resistant red natural rubber Reinforcement: Multiple plies of fabric with steel helix

Cover: Rubberized fabric

Temperature Range: -30°F (-35°C) to +140°F (+60°C)

Other rubber tubes available: SBR, EPDM



Specification Chart

Part No.	I.D.	WP	MBR	VAC	WT LBS/FT
3MBAF2RA02	2	30	10	29"	0.95
3MBAF2RA02.08	21/2	30	13	29"	1.13
3MBAF2RAO3	3	30	15	29"	1.40
3MBAF2RAO4	4	25	20	28"	1.98
3MBAF2RA05	5	20	25	26"	2.40
3MBAF2RA06	6	16	30	23"	2.85
3MBAF2RA07	7	14	35	18"	3.30
3MBAF2RA08	8	12	40	12"	3.75
3MBAF2RA10	10	10	50	8"	5.15
3MBAF2RA12	12	8	60	5"	6.15

All products are warranted to be free from all defects in material and workmanship. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete Terms and Conditions of Sale located on our web sites at: www.novaflex.com / www.z-flex.com / www.flexmaster.com.

05.2019

IN USA

North Carolina 449 Trollingwood Road Haw River, NC 27258 tel (336)578-2161 fax (336)578-5554 800-334-4270

New Jersey

1024 Industrial Drive West Berlin, NJ 08091 tel (856)768-2275 fax (856)768-2385 800-225-0215

Indianapolis

7812 Moller Road Indianapolis, IND 46268 tel (317)334-1444 fax (317)334-1535 800-526-6288

IN CANADA

Whitby, Ontario 119 Consumers Drive Whitby, ON L1N 1C4 tel (905)666-4970 fax (905) 666-9388 800-563-3539

IN U.K.

Bromborough, Wirral

18 Candy Park 2, Power Road Bromborough, Wirral UK CH62 3QT tel 44(0)151-334-0873 fax 44(0)151-334-7145

www.novaflex.co.uk Email: sales@novaflex.co.uk



Email: sales@novaflex.com Website: www.novaflex.com