









NovaFlex[®] Concrete Hose

HP Novacrete Novaflex 5787

High pressure hose designed to handle the pumping of concrete, plaster or grout mixture.

Specifications

Tube: Abrasion resistant synthetic rubber

Reinforcement: High tensile synthetic textile Cover: Black Abrasion, ozone and weather resistant synthetic rubber

Length: 100 ft

Temperature Range: -20°F to 160°F

Safety Factor: 2:1

			1000	
ID	OD	WP	Min Burst Pressure	-
1 ½	2.19	1233	2580	13
2	2.83	1233	2580	12
2 1/2	3.33	1233	2580	
3	4.01	1233	2580	
3 ½	4.65	1233	2580	
4	5.10	1233	2580	
5	6.09	1233	2580	1000
	1 ½ 2 ½ 3 ⅓ 3 ½ 4	1½ 2.19 2 2.83 2½ 3.33 3 4.01 3½ 4.65 4 5.10	1½ 2.19 1233 2 2.83 1233 2 2.83 1233 3 4.01 1233 3 4.65 1233 4 5.10 1233	Pressure 1½ 2.19 1233 2580 2 2.83 1233 2580 2½ 3.33 1233 2580 3 4.01 1233 2580 3½ 4.65 1233 2580 3½ 5.10 1233 2580







The Novaflex Group is a market leader through excellence in product innovation and design. The Novaflex Group is a privately held company committed to continuous advancement in hose and connector solutions. Novaflex has one of the broadest product ranges available in the hose and ducting marketplace, as well as the HVAC, Industrial Venting, Hose Industries and Commercial Exhaust Venting Systems. Products are sold in industries across North America and around the world.

U.S.A. Canada U.K. Bromborough, Wirral West Berlin, NJ Ajax, Ontario Indianapolis, IN **Burlington**, NC Tel: 44(0)151.334.0873 Tel: 336.578.2161 Tel: 905.686.5200 Tel: 856.768.2275 Tel: 317.334.1444 Fax: 905.686.8349 Fax: 44(0)151.334.7145 Fax: 856.768.2385 Fax: 317.334.1535 Fax: 336.578.5554 sales@novaflex.co.uk 800.225.0215 800.526.6288 800.334.4270

Website: www.novaflex.com Email: sales@novaflex.com